

TIPO	PESO		EXTERNO			MEDIDAS INTERNO			PUERTAS ABIERTAS			VOLUMEN	
	VACIO	PESO MÁX.	LARGO	ANCHO	ALTO	LARGO	ANCHO	ALTO	LARGO	ANCHO	ALTO		
DRY-VAN 20'	2.250 Kg	28.240 Kg	6.058 mm	2.438 mm	2.591 mm	5.900 mm	2.345 mm	2.400 mm		2.335 mm	2.290 mm	33,30 m3	
DRY-VAN 40'	3.630 Kg	26.850 Kg	12.192 mm	2.438 mm	2.591 mm	12.030 mm	2.345 mm	2.400 mm		2.335 mm	2.290 mm	67,70 m3	
DRY-VAN 40' HIGH CUBE	3.800 Kg	26.600 Kg	12.192 mm	2.438 mm	2.896 mm	12.030 mm	2.350 mm	2.710 mm		2.335 mm	2.595 mm	76,50 m3	
REEFER 20'	3.400 Kg	27.280 Kg	6.058 mm	2.438 mm	2.591 mm	5.500 mm	2.285 mm	2.255 mm		2.285 mm	2.210 mm	28,30 m3 180/200V y 380/440V 50/60 Hz // -25/+25°	
REEFER 40'	4.500 Kg	30.400 Kg	12.192 mm	2.438 mm	2.591 mm	11.575 mm	2.285 mm	2.250 mm		2.280 mm	2.200 mm	59,50 m3 380/440V 50/60 Hz // -25/+25°	
REEFER 40' HIGH CUBE	5.200 Kg	29.250 Kg	12.192 mm	2.438 mm	2.895 mm	11.575 mm	2.290 mm	2.550 mm		2.290 mm	2.435 mm	67,60 m3 380/440V 50/60 Hz // -25/+25°	
ABIERTO 20' OPEN TOP	2.250 Kg	28.230 Kg	6.058 mm	2.438 mm	2.591 mm	5.900 mm	2.330 mm	2.380 mm		2.330 mm ABERTURA SUPERIOR 5.740 mm	2.220 mm	31,80 m3	
ABIERTO 40' OPEN TOP	3.650 Kg	26.830 Kg	12.192 mm	2.438 mm	2.591 mm	12.045 mm	2.340 mm	2.380 mm		2.335 mm ABERTURA SUPERIOR 11.890 mm	2.255 mm	67,10 m3	
ABIERTO 20' FLAT RACK	2.500 Kg	30.150 Kg	6.058 mm	2.438 mm	2.591 mm	5.900 mm	2.400 mm	2.285 mm	5.700 mm	2.250 mm	2.285 mm		
ABIERTO 40' FLAT RACK	4.900 Kg	40.100 Kg	12.192 mm	2.438 mm	2.591 mm	12.150 mm	2.400 mm	2.035 mm	11.835 mm	2.230 mm	2.035 mm		